

ORDINARY INDICATOR

SLD17.5

IP30



Describing

- Colours: Red, Orange, Green, Blue.
- Dome: Polycarbonate resin with superior resistance to impact and heat.
- Stylish pole-type matching small automatic devices; requires little space for installation and is easy to mount.
- Prism-cut lens offers the brightest light.
- Colour can be changed easily thanks to screw-in lamp lens.
- Can be mounted upward, downward, or sideways.
- Vibration Resistance: 10~55HZ Frequency, 0.5mm amplitude in Y direction for 40 minutes.
- Shock resistance 500m/s² acceleration (approx. 50G) in Y direction for three times.

Dimensions



Type

FLASH Model	Rated Voltage	Bulb	Flashing Per Minute	Weight
SLD17.5-BB0C-R1	AC/DC 12V	12V 0.11W	60f.p.m	1.0kg
SLD17.5-BB0F-R1	AC/DC 24V	24V 0.11W		
SLD17.5-BB0M-R1	AC 110V	110V 3W		
SLD17.5-BB0N-R1	AC 220V	110V 3W		
CONTINUOUS Model	Rated Voltage	Bulb	Flashing Per Minute	Weight
SLD17.5-BA0C-R1	AC/DC 12V	12V 0.11W	—	0.7kg
SLD17.5-BA0F-R1	AC/DC 24V	24V 0.11W		
SLD17.5-BA0M-R1	AC 110V	110V 3W		
SLD17.5-BA0N-R1	AC 220V	110V 3W		