





## Thru-beam Mode (DC)






Ag: RP76 SERIES

Sensing Mode	Connection	Supply Voltage	Output Mode	Part Number
Infrared:880nm	Terminal 	10-30V DC	Emitter	RP76-T028MD-EY9T4L
			NPN	RP76-T028MN-CY9T4U
			PNP	RP76-T028MP-CY9T4U
			NPN/PNP	RP76-T028MD-CY9T4U
			NPN , Timing delay	RP76-T028MN-CY9T4U-T
			PNP , Timing delay	RP76-T028MP-CY9T4U-T
			NPN/PNP,Timing delay	RP76-T028MD-CY9T4U-T
	Quick Disconnect (0°or90°settled) 	10-30V DC (Euro Style)	Emitter	RP76-T028MD-EY9Q4LE
			NPN	RP76-T028MN-CY9Q4UE
			PNP	RP76-T028MP-CY9Q4UE
			NPN/PNP	RP76-T028MD-CY9Q4UE
			NPN , Timing delay	RP76-T028MN-CY9Q4UE-T
			PNP , Timing delay	RP76-T028MP-CY9Q4UE-T
			NPN/PNP,Timing delay	RP76-T028MD-CY9Q4UE-T
Thru-beam Mode Sensing Distance: 28m	Quick Disconnect swivel 90° 	10-30V DC (Euro Style)	Emitter	RP76-T028MD-EY9Q4LE-S
			NPN	RP76-T028MN-CY9Q4UE-S
			PNP	RP76-T028MP-CY9Q4UE-S
			NPN/PNP	RP76-T028MD-CY9Q4UE-S
			NPN , Timing delay	RP76-T028MN-CY9Q4UE-TS
			PNP , Timing delay	RP76-T028MP-CY9Q4UE-TS
			NPN/PNP,Timing delay	RP76-T028MD-CY9Q4UE-TS
	6" Pigtail 	10-30V DC (Euro Style)	Emitter	RP76-T028MD-EY9P4LE
			NPN	RP76-T028MN-CY9P4UE
			PNP	RP76-T028MP-CY9P4UE
			NPN/PNP	RP76-T028MD-CY9P4UE
			NPN , Timing delay	RP76-T028MN-CY9P4UE-T
			PNP , Timing delay	RP76-T028MP-CY9P4UE-T
			NPN/PNP,Timing delay	RP76-T028MD-CY9P4UE-T

Note:

Coming Soon : Part numbers with underline  
 In Preparation: Part numbers with a line through the middle  
 — Ag-01 —

## Thru-beam Mode (AC/DC)

Sensing Mode	Connection	Supply Voltage	Output Mode	Part Number
<b>Infrared: 880nm</b>  	<b>Terminal</b>  	<b>12-240V DC/ 24-240V AC</b>	Emitter (2-wire)	RP76-T028MA-EY9T4L
			Relay NO (4-wire)	RP76-T028MR-CY9T4L
			Relay NO, Timing delay (4-wire)	RP76-T028MR-CY9T4L-T
			SPST Solid-state Light-ON/Dark-ON (2-wire)	
	<b>Quick Disconnect (0° or 90° settled)</b>  	<b>12-240V DC/ 24-240V AC (Micro Style)</b>	Emitter (2-wire)	RP76-T028MA-EY9Q4LM
			Relay NO (4-wire)	RP76-T028MR-CY9Q4LM
			Relay NO, Timing delay (4-wire)	RP76-T028MR-CY9Q4LM-T
			SPST Solid-state Light-ON/Dark-ON (2-wire)	
	<b>Quick Disconnect swivel 90°</b>  	<b>12-240V DC/ 24-240V AC (Micro Style)</b>	Emitter (2-wire)	RP76-T028MA-EY9Q4LM-S
			Relay NO (4-wire)	RP76-T028MR-CY9Q4LM-S
			Relay NO, Timing delay (4-wire)	RP76-T028MR-CY9Q4LM-TS
			SPST Solid-state Light-ON/Dark-ON (2-wire)	
<b>Thru-beam Mode Sensing Distance: 28m</b>  	<b>12-240V DC/ 24-240V AC (Micro Style)</b>	Emitter (2-wire)	RP76-T028MA-EY9P4LM	
		Relay NO (4-wire)	RP76-T028MR-CY9P4LM	
		Relay NO, Timing delay (4-wire)	RP76-T028MR-CY9P4LM-T	
		SPST Solid-state Light-ON/Dark-ON (2-wire)		

**Note:**  
 Coming Soon : Part numbers with underline  
 In Preparation: Part numbers with a line through the middle  
 — Ag-02 —

Ag: RP76 SERIES